

RAY

DL19 - LOW GLARE LED RECESSED DOWNLIGHT

Visual Comfort













Aimed at increasing visual comfort, the Ray downlight from Vision Lighting is specifically designed to reducing eye strain and fatigue.


The Ray features a deep set LED chip, specular aluminium reflector on the inside and matte aluminium reflector on the outside, to work in combination and achieve a UGR <19.

For quick and easy installation, the Ray comes complete with a 1.2m flex and plug, and 2 spring clips.



PRODUCT SPECIFICATIONS

Wattage:	13W / 25W / 35W
Lumens:	1000-3350
Efficacy:	>95Lm/W
CCT:	3000K / 4000K
CRI:	>80
Beam Angle:	45°
Glare Rating:	UGR<19
Dimming:	None / Triac Universal / DALI
Material:	Aluminium housing
Reflector:	Specular Aluminium
Trim Colour:	White / (Black or Grey special order)
IP Rating:	IP20
Mounting:	Plaster recessed





RAY

DL19 - LOW GLARE LED RECESSED DOWNLIGHT

CODING METHODOLOGY

Family	Power		Lumens		ССТ		Trim Colour		Dimming	
DL19	13 25 35	13W 25W 35W	2550Lm	110mmØ 190mmØ 230mmØ	-3K -4K	3000K 4000K	(Blank) -SLV -BLK	White Silver Black	(Blank) -D -DALI	None Triac Universal DALI

DIMENSIONAL DIAGRAM

