

PRESTIGE

FLE14 - LED FLOODLIGHT



Vision Lighting presents the eye-catching, Prestige range of floodlight luminaires. Sleek, robust and functional and with an exceptional IP66 rating, the Prestige is ideal for exterior architectural illumination.

Featuring a unique two body design for excellent heat distribution, the Prestige ensures LED stability and a long 50,000 hour life.

Utilising quality componentry in the form of Cree LEDs and a Meanwell driver, the body is constructed from a die-cast aluminum body and finished with a tempered glass surface plate.

Available in a number of beam options along with rotatable base plate or trunnion mounting options, the Prestige is a stunning edition to any quality lighting project.



PRODUCT SPECIFICATIONS

Wattage:	22W / 30W / 36W
Lumens:	1430 / 1950 / 2340Lm
Efficacy:	>65 Lm/W
CCT:	4000K
CRI:	>80
Beam Angle:	12.5°, 30°, 60°, 15x30°, 10x60°
Material:	Die-cast Aluminium
IP Rating:	IP66
IK Rating:	IK08
Mounting:	Baseplate or Trunnion
Driver:	Meanwell
Light Source:	Cree
Lifetime:	50,000hrs

PRESTIGE

FLE14 - LED FLOODLIGHT

CODING METHODOLOGY

Family	Power			CCT		Beam angle		Mounting	
FLE14	-22W	22W	1430 Lm	-4K	4000K	-12D	12.5 Degrees	(Blank)	Base Plate
	-30W	30W	1950 Lm			-30D	30 Degrees	-SM	Trunnion
	-36W	36W	2340 Lm			-60D	60 Degrees		
						-15X30D	15 x 30 Degrees		
						-10X60D	10 x 60 Degrees		

DIMENSIONAL DIAGRAM

