

MAESTRO

FLE22 - LED FLOODLIGHT



The Maestro from Vision Lighting is specifically design to provide excellent illumination efficacy.



Weatherproof, the Maestro is constructed from a smooth, seamless and compact aluminium body to IP65. Incorporating a high transmittance polycarbonate lens the Maestro offers a variety of beam angles.

Incorporating quality LED componentry, the Maestro is available in a variety of wattages and includes a $\pm 90^\circ$ adjustable mounting bracket to enable precise aiming for exterior floodlighting applications.



PRODUCT SPECIFICATIONS

Wattage:	50W / 70W / 90W
Lumens:	5750Lm / 8050Lm / 10350Lm
Efficacy:	115Lm/W
CCT:	4000K / 5000K
CRI:	>Ra70
Material:	Aluminium
Diffuser:	Polycarbonate
Colour:	Black
IP Rating:	IP65
IK Rating:	IK07 with PC lens
Mounting:	Trunnion Bracket
Driver:	Meanwell
Lifetime:	>50,000hrs



MAESTRO

FLE22 - LED FLOODLIGHT

CODING METHODOLOGY

Family	Power		Lumens	CCT		Beam Angle	
FLE22	50	50W	5750Lm	-4K	4000K	-75X100D	75x100 Degrees
	70	70W	8050Lm	-5K	5000K	-100D	Glass
	90	90W	10350Lm				

DIMENSIONAL DIAGRAM

