

# GALAXY 65

## HLE20 - LINEAR LED WEATHERPROOF HIGHBAY

### *Durable & Lightweight*



Constructed to IP65 from premium grade aluminum die-cast housing and stainless steel hardware, the Vision Galaxy 65 is durable, lightweight and built for industrial and commercial applications.

Incorporating high quality LED componentry to achieve >90Lm/W output and an impressive 50,000 hour life, the luminaire also features a unique patented thermal management design to ensure low LED junction temperature.


Ideal where simple installation and maintenance is required, the Galaxy 65 Highbay luminaire is the perfect lighting solution for warehouse and production applications.

Additional options include; 1-10V or DALI dimming and lenses for wide or narrow beam patterns.



### PRODUCT SPECIFICATIONS

<b>Wattage:</b>	50W / 100W /150W / 200W
<b>Lumens:</b>	5,400 - 21,500 Lm
<b>Efficacy:</b>	>90Lm/W
<b>CCT:</b>	5000K
<b>CRI:</b>	Ra80
<b>Beam Angle:</b>	Multiple Options
<b>Dimming:</b>	DALI / 1-10V
<b>Material:</b>	Aluminium
<b>Diffuser:</b>	Transparent PC
<b>Colour:</b>	White Satin Finish
<b>IP Rating:</b>	IP65
<b>Mounting:</b>	Suspended
<b>Driver:</b>	Meanwell



# GALAXY 65

## HLE20 - LINEAR LED WEATHERPROOF HIGHBAY

### CODING METHODOLOGY

Family	Power	Lumens	CCT	Beam angle	Dimming
<b>HLE20</b>	<b>50</b> 50W	5,400 Lm		<b>-15X110</b> 15x110 Degrees	
	<b>100</b> 100W	10,700 Lm	<b>-4K</b> 4000K	<b>-30X110</b> 30x110 Degrees	<b>(Blank)</b> None
	<b>150</b> 150W	16,000 Lm	<b>-5K</b> 5000K	<b>-40X110</b> 40x110 Degrees	<b>-DA</b> DALI
	<b>200</b> 200W	21,500 Lm		<b>-110D</b> 110x110 Degrees	<b>-D</b> 1-10V Dimmable

### DIMENSIONAL DIAGRAM

