

GLIDE

TL22 - CYLINDRICAL LED TRACK LIGHT

Versatile Illumination



The Glide range of LED track luminaires from Vision Lighting provide exceptional flexibility for both general and feature illumination.


The versatile track set up allows for unparalleled flexibility and the ability to position the Glide as desired on the track mounting. The 350° horizontal rotation and 90° vertical rotation ensures the ability to aim light where it is required.

Constructed from die-cast aluminium, the Glide is also available in a variety of wattages and beam angles to meet your project requirements.



PRODUCT SPECIFICATIONS

Wattage:	12W / 19W / 25W / 28W
Lumens:	960Lm / 1600Lm / 2000Lm/ 2400Lm
Efficacy:	>80Lm/W
CCT:	3000K / 4000K
CRI:	>80
Beam Angle:	15 / 24 / 36 Degrees
Material:	Die-Cast Aluminium
Reflector:	Aluminium
Colour:	White / Black
IP Rating:	IP20
Mounting:	3 Circuit track
Driver:	Tridonic
Light Source:	Luminus



GLIDE

TL22 - CYLINDRICAL LED TRACK LIGHT


CODE BUILDER

Family	Power		Lumens	CCT		Beam Angle		Trim Colour		Dimming	
TL22	12	12W	960Lm	-3K	3000K	-15D	15 Degrees	-WT	White	(Blank)	None
	19	19W	1600Lm	-4K	4000K	-24D	24 Degrees	-BK	Black		
	25	25W	2000Lm			-36D	36 Degrees				
	28	28W	2400Lm								
e.g. TL2219-3K-24D-WT											



e.g. TL2219-3K-24D-WT

DIMENSIONAL DIAGRAM



12W




19W / 25W



28W



Angle Adjustment



GLIDE

TL22 - CYLINDRICAL LED TRACK LIGHT

GLARE SHIELD ACCESSORIES

Accessories available for this track light include a visor glare shield, an adjustable 'barn-door' glare shield for greater control, and a honey-comb louver glare shield.

