

CIBSE

LIG053
LIG054
LIG058
LIG910
LIG953
LIG9004

DARAY[®]
Medical

Product Datasheet

Examination Light

X700

LED



Introduction

The DARAY X700 LED examination light is both powerful and incredibly flexible, featuring variable colour adjustment. Utilising LED technology, the general examination light has been developed to provide an intense beam with excellent colour rendering properties.

The X700 LED forms part of the **X700 Range**, which comprises the following models: X700, X710, X730, X740.

All models in the X700 Range offer identical light output, though with differing mounting/wiring options:

X700 - Same as X740, though with a flexible 'gooseneck' instead of the articulated (spring-balanced) arm.

X710 - Available as a wall/rail mount solution with an integrated transformer, to be hardwired.

X730 - Provides a panel mount bracket and an angled neck for mounting to bed-head trunking, to be hardwired.

X740 - Same as X700, though with an articulated (spring-balanced) arm instead of the flexible 'gooseneck'.

Datasheets are available for each model in this Range.

Standard Features

- World-renowned LED technology
- Variable intensity
- Variable colour temperature
- Flexible gooseneck for versatile movement and solid positioning
- Excellent colour rendering
- A strong beam of light with an even intensity across the entire area for clearer viewing and reduced eye strain
- Fully positionable light head
- Various mounting options available
- Energy-efficient, environmentally friendly, and a fully recyclable product

Available Options

X700LW	DARAY X700 LED wall mounted examination light
X700LR	DARAY X700 LED rail mounted examination light (rail sold separately - see XRAIL below)
X700LD	DARAY X700 LED desk clamp examination light
X700LDS	DARAY X700 LED desk stand examination light
X700LFDM	DARAY X700 LED fixed desk mount examination light
X700LM	DARAY X700 LED mobile examination light
XRAIL	1m Medical Rail for mounting X700LR (includes wall fixings)
XBB12	Battery back-up options available, please call
Bespoke solutions available, please call	

Technical Specifications

Light Source	LED
Light Intensity (Lux) @ 0.5m	80,000 Lux \pm 5%
Light Intensity (Lux) @ 0.75m	40,000 Lux \pm 5%
Light Intensity (Lux) @ 1.0m	20,000 Lux \pm 5%
Light Intensity Adjustment Range	25 - 100%
Colour Temperature (Kelvin)	3,600K - 5,000K (\pm 500K)
Colour Rendering Index (CRI)	95
Colour Rendering (R9)	95
Light Field Diameter (D50)	@ 0.5m: 60mm
	@ 0.75m: 90mm
	@ 1.0m: 120mm
Light Field Diameter (D10)	@ 0.5m: 110mm
	@ 0.75m: 150mm
	@ 1.0m: 200mm
Number of LED's	4
Power Consumption	16W 0.14A
Average Working Life	>40,000 Hours
Input Supply Rating	100 - 240V AC 50/60 Hz
Output Supply Rating	12V DC 1A
Temperature Rise on Patient/User	\leq 2°C
Warranty Period	5 Years
NHS E-Class Code	FBU, FKR
Commodity Code	9018 908400
GMDN Code	12276

Medical Approvals/Certificates

The product(s) on this datasheet adhere to the following standards in line with the 93/42/EEC Medical Devices Directive - Classification: Class 1, Rule 1.

EN 13485	EN 60601-1-2
EN 14971	EN 60601-2-41
EN 9001	EN 60601-1-6
EN 60601-1	EN 1041
2014/35/EU Low Voltage Directive	EN 60598-2-25


Notes

Our X700 Range is available with a wide array of mounting options to ensure your light is exactly where you need it. Available in two arm options (flexible gooseneck or spring-balanced arm) and a large range of plug-top and hardwired mounting options to suit all clinical needs.

This model features a low total cost of ownership, costing up to 75% less to run than equivalent halogen lights. This light has around 40,000 hours of life from the LED light engine equating to around 20 years of clinical use. The X700 Range requires minimal maintenance and is an ideal light for GP surgeries and clinics where flexibility and performance are crucial.

Technical Drawings

X700 LED Wall Mount
Code: X700LW
Same dimensions apply for all other versions



Mounting Options

These are DARAY's standard mounting options, and are all **interchangeable**.



If you are looking for a hardwired version of the X700; see the Datasheet for the X710 model.

Image Gallery



(UK Customers only)



X700 LED Mobile
Code: X700LM
5-metre cable supplied



X700 LED Wall Mount
Code: X700LW



Code: X700LFDM



Code: X700LDS



Code: X700LD



X700 LED Rail Mount
Code: X700LR
(shown here on XRAIL Medical Rail - available separately)



Digital control panel
Features: Power on/off
Light intensity adjustment
Colour temp adjustment

Removable autoclavable handle